



Ditta Forte S de RL de CV  
Camino a la Tijera 806 Int B1, La Tijera Tlajomulco de Zuliga Jalisco C.P 45645  
www.dittaforte.com.mx  
Email: [contactanos@dittaforte.com.mx](mailto:contactanos@dittaforte.com.mx)  
Phone: (33) 1204-0664

## Aluminum Composite Panel Specification

### ACM total Thickness Range:

2mm-8mm

### Aluminum Thickness Range:

0.08mm 0.10mm 0.12mm 0.15mm 0.2mm 0.25mm 0.3mm 0.35mm 0.4mm 0.45mm 0.5mm

### ACM Width:

1220mm, 1250mm, 1500mm, 1550mm, 1570mm

### ACM length:

Less than 6m.

### Coating:

\*Polyester Coating: used for digital printing.

Matt Polyester usually has better digital printing effort than Gloss Polyester

\*PVDF: used for outdoor big projects. Like Alucobond, Alpolic

Warranty for PVDF is 15-20 years not change color under sunshine.

\*FEVE: used for outdoor big projects. Like Alucobond, Alpolic

Warranty for PVDF is 10-15 years not change color under sunshine. All FEVE is gloss color.

### Plastic core:

LDPE, low density polyethylene. It's black color

上海阿路那裝飾材料有限公司  
SHANGHAI ALUCORNTDECORATIVE MATERIAL CO.,LTD.  
朱榮平